



WhisperRoom^{INC.}

MDL 4284SNV (3.5' x 7')

Base Price: \$3,530*

* USD. Does not include optional features or shipping.

BASIC FEATURES

- 5 Year Warranty
- 12" x 30" Door Window
- 6 Acoustical Foam Sheets
- 1-24" Fluorescent Light
- 4 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Windows (WDO) 4 Sizes
- Ventilation System w/remote switch
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Caster Plate (CP)
- Exterior Accent Package (EAP)
- Soundwave Deflection System (SDS)
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)

ASSEMBLY TIME

Approximately 2 hours

ASSEMBLED WEIGHT

875lbs 396kg **NOTE:** Optional features may increase weight.

EXTERIOR DIMENSIONS

| | | | |
|--------------|--------|-------|--|
| Height: | 6' 11" | 211cm | NOTE: No Ventilation models are configured for, but do not include ventilation. Ventilation systems can be added at any time. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed. |
| Dimension 1: | 3' 8" | 112cm | |
| Dimension 2: | 7' 2" | 218cm | |

INTERIOR DIMENSIONS

| | | | |
|--------------|--------|-------|---|
| Height: | 6' 8" | 203cm | NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface. |
| Dimension 1: | 3' 4" | 102cm | |
| Dimension 2: | 6' 10" | 208cm | |

WALL CONSTRUCTION

| | | | |
|------------------|--------------|----------------|-----------------|
| Total Thickness: | 3" | 7.62cm | |
| | 1" | 2.54cm | MDF Barrier |
| | 2" | 5.08cm | Detachable Foam |
| Weight: | 3.2 lbs/sqft | 15.66 kg/sqmtr | |

DOOR WINDOW DESIGN

| | | | |
|------------------|-----------|-------------------|------------------------|
| Total Thickness: | 3/4" | 19.05mm | |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| | 1/4" | 6.35mm | Air |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| Size: | 12" x 30" | 30.48cm x 76.20cm | |

NOISE REDUCTION

| | | | | | | |
|--------------------|-----|-----|-----------------------------|------|------|------|
| | | | <u>Accurate to +/- 3 dB</u> | | | |
| Frequency (Hertz): | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| Reduction (dB): | 29 | 36 | 43 | 45 | 48 | 52 |