



# MDL 4872S (4' x 6')

**Base Price: \$4,375\***

*\* USD. Does not include optional features or shipping.*

## BASIC FEATURES

- 5 Year Warranty
- 1 Ventilation System w/Remote Switch
- 6 Acoustical Foam Sheets
- 12" x 30" Door Window
- 1-24" Fluorescent Light
- 2 Cable Passages

## OPTIONAL FEATURES

(Not included in Base Price)

- Wall Windows (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System(VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Exterior Accent Package(EAP)
- Soundwave Deflection System(SDS)
- 10" Height Extension (HX)
- Exterior Fan Silencer(EFS)
- XLR Jack Panel (XLR) 8 Jacks

## ASSEMBLY TIME

Approximately 1.5 hours

## ASSEMBLED WEIGHT

880lbs      399kg

**NOTE:** Optional features may increase weight.

## EXTERIOR DIMENSIONS

Height:            6' 11"      211cm  
 Dimension 1:    4' 2"      127cm  
 Dimension 2:    6' 2"      188cm

**NOTE:** Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 1/2 inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.

## INTERIOR DIMENSIONS

Height:            6' 8"      203cm  
 Dimension 1:    3' 10"     117cm  
 Dimension 2:    5' 10"     178cm

**NOTE:** Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

## WALL CONSTRUCTION

Total Thickness: 3"      7.62cm  
                           1"      2.54cm      MDF Barrier  
                           2"      5.08cm      Detachable Foam

Weight:            3.2 lbs/sqft    15.66 kg/sqmtr

## DOOR WINDOW DESIGN

Total Thickness: 3/4"      19.05mm  
                           1/4"      6.35mm      Laminated Safety Glass  
                           1/4"      6.35mm      Air  
                           1/4"      6.35mm      Laminated Safety Glass

Size:                12" x 30"      30.48cm x 76.20cm

## NOISE REDUCTION

Accurate to +/- 3 dB

Frequency (Hertz):	125	250	500	1000	2000	4000
Reduction (dB):	29	36	43	45	48	52