

MDL 6084 S (5' x 7')

BASIC FEATURES

- 5 Year Warranty
- 2 Ventilation Systems w/Remote Switch
- 7 Acoustical Foam Sheets

- 12" x 30" Door Window
- 1-24" Fluorescent Light
- 4 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)

- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME		Approximatel	y 2.5 hours		
ASSEMBLED WEIGHT		1050lbs	476kg	NOTE: Optional features may increase weight.	
EXTERIOR DIMENSIONS	Height: Dimension 1: Dimension 2:	6' 11" 5' 2" 7' 2"	211cm 158cm 218cm	NOTE: Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 ½ inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.	
INTERIOR DIMENSIONS	Height: Dimension 1: Dimension 2:	6' 8" 4' 10" 6' 10"	203cm 147cm 208cm	NOTE : Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.	
WALL CONSTRUCTION	Total Thickness:	3"	7.62cm		
		1" 2"	2.54cm 5.08cm	MDF Barrier Detachable Foam	
	Weight:	3.2 lbs/sqft	15.66 kg/sc	z/sqmtr	
DOOR WINDOW DESIGN	Total Thickness:	3/4" 1/4" 1/4" 1/4"	19.05mm 6.35mm 6.35mm 6.35mm	Laminated Safety Glass Air Laminated Safety Glass	
	Size:	12" x 30"	30.48cm x 76.20cm		

NOISE REDUCTION Accurate to +/- 3 dB

Frequency (Hertz): 125 250 500 1000 2000 4000 Reduction (dB): 29 36 43 45 48 52