



MDL 7272 E (6' x 6')

BASIC FEATURES

- 5 Year Warranty
- 2 Ventilation Systems w/Remote Switch
- 7 Acoustical Foam Sheets
- 16" x 30" Door Window
- 1-24" Fluorescent Light
- 4 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME

Approximately 5 hours

NOTE: Optional features may increase weight.

ASSEMBLED WEIGHT

2015 lbs 913 kg

NOTE: Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 1/2 inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.

EXTERIOR DIMENSIONS

Height:	7' 1"	216 cm
Dimension 1:	6' 2"	189 cm
Dimension 2:	6' 2"	189 cm

INTERIOR DIMENSIONS

Height:	6' 8"	203 cm
Dimension 1:	5' 5.5"	170 cm
Dimension 2:	5' 5.5"	170 cm

NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

O	IO	otal thickness:	5 1/4"	13.34cm			
			1"	2.54cm	MDF Barrier		
			1 1/4"	3.18cm	Air/Foam		
			1"	2.54cm	MDF Barrier		
			2"	5.08cm	Detachable Foam		
				Weight:	6.5 lbs/sqft	31.80kg/sqmt	
		225 [1] 12 [6] [1]			3 1/8"	7.94cm	
					1/4"	6.35mm	Laminated Safety Glass
					1/4"	6.35mm	Air
					1/4"	6.35mm	Laminated Safety Glass
1 5/8"	4.13cm				Air		
1/4"	6.35mm				Laminated Safety Glass		
1/4"	6.35mm				Air		
1/4"	6.35mm				Laminated Safety Glass		
		6 [1] [1]	16" x 30"	30.48cm x 76.20cm			

NOISE REDUCTION

Accurate to +/- 3 dB

Frequency (Hertz):	125	250	500	1000	2000	4000
Reduction (dB):	30	44	53	61	67	68