



## MDL 84126 S (7' x 10.5')

### BASIC FEATURES

- 5 Year Warranty
- 4 Ventilation Systems w/Remote Switch
- 9 Acoustical Foam Sheets
- 12" x 30" Door Window
- 2-24" Fluorescent Lights
- Configured for Ventilation

### OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

### ASSEMBLY TIME

Approximately 3.5 hours

### ASSEMBLED WEIGHT

1725lbs      781kg

**NOTE:** Optional features may increase weight.

### EXTERIOR DIMENSIONS

Height:	6' 11"	211cm
Dimension 1:	7' 2"	218cm
Dimension 2:	10' 8"	325cm

**NOTE:** Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 1/2 inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.

### INTERIOR DIMENSIONS

Height:	6' 8"	203cm
Dimension 1:	6' 10"	208cm
Dimension 2:	10' 4"	315cm

**NOTE:** Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

### WALL CONSTRUCTION

Total Thickness:	3"	7.62cm	
	1"	2.54cm	MDF Barrier
	2"	5.08cm	Detachable Foam
Weight:	3.2 lbs/sqft	15.66 kg/sqmtr	

### DOOR WINDOW DESIGN

Total Thickness:	3/4"	19.05mm	
	1/4"	6.35mm	Laminated Safety Glass
	1/4"	6.35mm	Air
	1/4"	6.35mm	Laminated Safety Glass
Size:	12" x 30"	30.48cm x 76.20cm	

### NOISE REDUCTION

	<u>Accurate to +/- 3 dB</u>					
Frequency (Hertz):	125	250	500	1000	2000	4000
Reduction (dB):	29	36	43	45	48	52