



MDL 96120 S (8' x 10')

BASIC FEATURES

- 5 Year Warranty
- 3 Ventilation Systems w/Remote Switch
- 11 Acoustical Foam Sheets
- 16" x 30" Door Window
- 2-24" Fluorescent Lights
- 6 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Windows (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME

Approximately 3 hours

ASSEMBLED WEIGHT

1798 lbs 815 kg

EXTERIOR DIMENSIONS

Height:	6' 11"	211 cm
Dimension 1:	8'	244 cm
Dimension 2:	10'	305 cm

INTERIOR DIMENSIONS

Height:	6' 8"	203 cm
Dimension 1:	7' 10"	239 cm
Dimension 2:	9' 10"	300 cm

NOTE: Optional features may increase weight.

NOTE: Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 1/2 inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70cm) if an optional caster plate is installed.

NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08cm) thick acoustical foam which attaches and partially covers the interior wall surface.

WALL CONSTRUCTION

Total Thickness:	3"	7.62 cm	
	1"	2.54 cm	MDF Barrier Detachable
	2"	5.08 cm	Foam
Weight:	3.2 lbs/sq ft	15.66 kg/sq mtr	

DOOR WINDOW DESIGN

Total Thickness:	3/4"	19.05 mm	
	1/4"	6.35 mm	Laminated Safety Glass
	1/4"	6.35 mm	Air
	1/4"	6.35 mm	Laminated Safety Glass
Size:	16" x 30"	40.60 cm x 76.20 cm	

NOISE REDUCTION

			Accurate to +/- 3 dB			
Frequency (Hertz):	125	250	500	1000	2000	4000
Reduction (dB):	29	36	43	45	48	52