



MDL 4260 E (3.5' x 5')

BASIC FEATURES

- 5 Year Warranty
- 1 Ventilation System w/Remote Switch
- 4 Acoustical Foam Sheets
- 12" x 30" Door Window
- 1-24" Fluorescent Light
- 2 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME

Approximately 3 hours

ASSEMBLED WEIGHT

1205lbs 546kg

NOTE: Optional features may increase weight.

EXTERIOR DIMENSIONS

Height: 7' 1" 216cm
 Dimension 1: 3' 8" 112cm
 Dimension 2: 5' 2" 158cm

NOTE: Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 ½ inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.

INTERIOR DIMENSIONS

Height: 6' 8" 203cm
 Dimension 1: 2' 11.5" 90cm
 Dimension 2: 4' 5.5" 136cm

NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

WALL CONSTRUCTION

Total Thickness: 5 1/4" 13.34cm
 1" 2.54cm MDF Barrier
 1 1/4" 3.18cm Air/Foam
 1" 2.54cm MDF Barrier
 2" 5.08cm Detachable Foam

Weight: 6.5 lbs/sqft 31.80kg/sqmtr

DOOR WINDOW DESIGN

Total Thickness: 3 1/8" 7.94cm
 1/4" 6.35mm Laminated Safety Glass
 1/4" 6.35mm Air
 1/4" 6.35mm Laminated Safety Glass
 1 5/8" 4.13cm Air
 1/4" 6.35mm Laminated Safety Glass
 1/4" 6.35mm Air
 1/4" 6.35mm Laminated Safety Glass

Size: 12" x 30" 30.48cm x 76.20cm

NOISE REDUCTION

Accurate to +/- 3 dB

Frequency (Hertz):	125	250	500	1000	2000	4000
Reduction (dB):	30	44	53	61	67	68