



MDL 6084 E (5' x 7')

BASIC FEATURES

- 5 Year Warranty
- 2 Ventilation Systems w/Remote Switch
- 7 Acoustical Foam Sheets
- 12" x 30" Door Window
- 1-24" Fluorescent Light
- 4 Cable Passages

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME

Approximately 5 hours

ASSEMBLED WEIGHT

1845lbs

836kg

NOTE: Optional features may increase weight.

EXTERIOR DIMENSIONS

| | | |
|--------------|-------|-------|
| Height: | 7' 1" | 216cm |
| Dimension 1: | 5' 2" | 158cm |
| Dimension 2: | 7' 2" | 218cm |

NOTE: Exterior Dimensions 1 & 2 do not include ventilation ducting which protrudes an additional 5 1/2 inches (13.97cm) off of one or more exterior walls, depending on unit size and configuration chosen. Exterior height is increased by 5 inches (12.70 cm) if an optional caster plate is installed.

INTERIOR DIMENSIONS

| | | |
|--------------|---------|-------|
| Height: | 6' 8" | 203cm |
| Dimension 1: | 4' 5.5" | 136cm |
| Dimension 2: | 6' 5.5" | 197cm |

NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

WALL CONSTRUCTION

| | | | |
|------------------|--------------|---------------|-----------------|
| Total Thickness: | 5 1/4" | 13.34cm | |
| | 1" | 2.54cm | MDF Barrier |
| | 1 1/4" | 3.18cm | Air/Foam |
| | 1" | 2.54cm | MDF Barrier |
| | 2" | 5.08cm | Detachable Foam |
| Weight: | 6.5 lbs/sqft | 31.80kg/sqmtr | |

DOOR WINDOW DESIGN

| | | | |
|------------------|-----------|-------------------|------------------------|
| Total Thickness: | 3 1/8" | 7.94cm | |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| | 1/4" | 6.35mm | Air |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| | 1 5/8" | 4.13cm | Air |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| | 1/4" | 6.35mm | Air |
| | 1/4" | 6.35mm | Laminated Safety Glass |
| Size: | 12" x 30" | 30.48cm x 76.20cm | |

NOISE REDUCTION

Accurate to +/- 3 dB

| | | | | | | |
|--------------------|-----|-----|-----|------|------|------|
| Frequency (Hertz): | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| Reduction (dB): | 30 | 44 | 53 | 61 | 67 | 68 |