



MDL 7296 ENV (6' x 8')

BASIC FEATURES

- 5 Year Warranty
- 7 Acoustical Foam Sheets
- 16" x 30" Door Window
- 1-24" Fluorescent Light
- 4 Cable Passages
- Configured for Ventilation

OPTIONAL FEATURES

(Not included in Base Price)

- Wall Window (WDO) 4 Sizes
- Caster Plate (CP)
- Ventilation System w/Remote Switch
- Ventilation Silencing System (VSS)
- Wide Access Door (WA)
- Audio Jack Panel (AJP) 6 or 10 Jacks
- Step (for use with Caster Plate)
- Studio Light Package
- 10" Height Extension (HX)
- Exterior Fan Silencer (EFS)
- XLR Jack Panel (XLR) 8 Jacks
- Acoustic Tuning Package (ATP)
- Elevated Floor Package (EFP)

ASSEMBLY TIME

Approximately 5 hours

ASSEMBLED WEIGHT

2330 lbs 1055 kg

NOTE: Optional features may increase weight.

EXTERIOR DIMENSIONS

| | | |
|--------------|-------|--------|
| Height: | 7' 1" | 216 cm |
| Dimension 1: | 6' 2" | 189 cm |
| Dimension 2: | 8' 2" | 250 cm |

NOTE: Interior Dimensions 1 & 2 do not include 2" (5.08 cm) thick acoustical foam which attaches and partially covers the interior wall surface.

INTERIOR DIMENSIONS

| | | |
|--------------|---------|--------|
| Height: | 6' 8" | 203 cm |
| Dimension 1: | 5' 5.5" | 170 cm |
| Dimension 2: | 7' 5.5" | 228 cm |

WALL CONSTRUCTION

| | | | |
|------------------|---------------|-----------------|-----------------|
| Total Thickness: | 5 1/4" | 13.34 cm | |
| | 1" | 2.54 cm | MDF Barrier |
| | 1 1/4" | 3.18 cm | Air/Foam |
| | 1" | 2.54 cm | MDF Barrier |
| | 2" | 5.08 cm | Detachable Foam |
| Weight: | 6.5 lbs/sq ft | 31.80 kg/sq mtr | |

DOOR WINDOW DESIGN

| | | | |
|------------------|-----------|---------------------|------------------------|
| Total Thickness: | 3 1/8" | 7.94 cm | |
| | 1/4" | 6.35 mm | Laminated Safety Glass |
| | 1/4" | 6.35 mm | Air |
| | 1/4" | 6.35 mm | Laminated Safety Glass |
| | 1 5/8" | 4.13 cm | Air |
| | 1/4" | 6.35 mm | Laminated Safety Glass |
| | 1/4" | 6.35 mm | Air |
| | 1/4" | 6.35 mm | Laminated Safety Glass |
| Size: | 16" x 30" | 30.48 cm x 76.20 cm | |

NOISE REDUCTION

| | Accurate to +/- 3 dB | | | | | |
|--------------------|----------------------|-----|-----|------|------|------|
| Frequency (Hertz): | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| Reduction (dB): | 30 | 44 | 53 | 61 | 67 | 68 |